

# Series 601, 602, 604 and 605

## 316 Stainless Steel Flexible Hoses

Series 601 hoses are constructed of 1/4" I.D. teflon® lined stainless steel braid, rated for 3000 psig. The 601 hoses are fitted with 1/4" NPT brass end connections; they make excellent economical manifold pigtails. The 602 hoses are fitted with 1/4" NPT stainless steel end connections.

The Series 604 hoses are constructed of double braided stainless steel, fitted with stainless steel 1/4" NPT end connections, rated for 3000 psig, and cleaned for oxygen service.



### 601 and 602 Features

- 1/4" I.D. Teflon® Lined 316 Stainless Steel Braided Hose
- Rated for 3000 PSIG
- 601 1/4" FNPT x 1/4" FNPT  
601M 1/4" MNPT x 1/4" MNPT  
601MF 1/4" MNPT x 1/4" FNPT
- 602 SS 1/4" FNPT x SS 1/4" FNPT  
602M SS 1/4" MNPT x SS 1/4" MNPT  
602MF SS 1/4" MNPT x SS 1/4" FNPT
- Cleaned for Oxygen Service.

### 604 and 605 Features

- 1/4" I.D. 316 Stainless Steel Double Braided Hose (605 Series has protective outer armor to provide greater safety and kink resistance.)
- Rated for 3000 PSIG
- 1/4" NPT Female or Male Stainless Steel End Connections
- Cleaned for Oxygen Service.
- Recommended for Helium and Hydrogen Service.

#### Special Hoses

We can provide any of the hoses on this page in different lengths and with a wide variety of end fittings.

### How to Order:

Model Number	Hose Length	Model Number	Hose Length	Model Number	Hose Length
601-2	2.0 feet	602-3	3.0 feet	604-6	6.0 feet
601M-2	2.0 feet	602M-3	3.0 feet	604M-6	6.0 feet
601MF-2	2.0 feet	602MF-3	3.0 feet	604MF-6	6.0 feet
601-3	3.0 feet	602-6	6.0 feet	605-2	2.0 feet
601M-3	3.0 feet	602M-6	6.0 feet	605M-2	2.0 feet
601MF-3	3.0 feet	602MF-6	6.0 feet	605MF-2	2.0 feet
601-6	6.0 feet	604-2	2.0 feet	605-3	3.0 feet
601M-6	6.0 feet	604M-2	2.0 feet	605M-3	3.0 feet
601MF-6	6.0 feet	604MF-2	2.0 feet	605MF-3	3.0 feet
602-2	2.0 feet	604-3	3.0 feet	605-6	6.0 feet
602M-2	2.0 feet	604M-3	3.0 feet	605M-6	6.0 feet
602MF-2	2.0 feet	604MF-3	3.0 feet	605MF-6	6.0 feet